



Spændebånd - Clamps

SPÆNDEBÅND. 12 MM BÅND 12 MM ENDLESS WORMDRIVE HOSE CLAMPS

928094 - 928096



KODE 928094. 12 mm bånd af rustfrit stål AISI 430. Hus af rustfrit stål AISI 430. Rustfri stålskrue galvaniseret bikromat.

KODE 928096. 12 mm bånd af rustfrit stål AISI 304. Hus af rustfrit stål AISI 304. Rustfri stålskrue AISI 304.

COD 928094. W2 Endless wormdrive hose clamps. Stainless steel band AISI 430 of 12 mm. Stainless steel housing AISI 430. Stainless steel screw galvanized bichromate.

COD 928096. W4 Endless wormdrive hose clamps. Stainless steel band AISI 304 of 12 mm. Stainless steel housing AISI 304. Stainless steel screw AISI 304.

W2-W4 mm 12				
SPÆNDEBÅND MÅL MIN/MAX CLAMPING RANGE MIN/MAX	SPÆNDEBÅND MÅL MIN/MAX CLAMPING RANGE MIN/MAX	MOMENT VED MONTAGE TORQUE - AT FITTING	MAX. MOMENT BRUDSTYRKE TORQUE - AT BREAK	ANTAL I KASSE PIECES FOR BOX
mm	tommer	Nm	Nm	Styk
16-25	5/8-1	≥ 5	≥ 6,5	50
20-32	25/32-1/4	≥ 5	≥ 6,5	50
25-40	0,90-1,57	≥ 5	≥ 6,5	50
32-50	1 1/4-2	≥ 5	≥ 6,5	50
40-60	19/16-2,36	≥ 5	≥ 6,5	50
50-70	2-2 3/4	≥ 5	≥ 6,5	10
60-80	2,36-3,15	≥ 5	≥ 6,5	10
70-90	2 3/4-3,54	≥ 5	≥ 6,5	10
80-90	3,15-3,94	≥ 5	≥ 6,5	10
90-110	3,54-4,33	≥ 5	≥ 6,5	10
100-120	3,94-4,72	≥ 5	≥ 6,5	10
110-130	4,33-5,12	≥ 5	≥ 6,5	10
120-140	4,72-5,51	≥ 5	≥ 6,5	10
130-150	5,12-5,91	≥ 5	≥ 6,5	10
140-160	5,91-6,3	≥ 5	≥ 6,5	10
150-170	5,91-6,69	≥ 5	≥ 6,5	10
160-180	6,3-7,09	≥ 5	≥ 6,5	10
170-190	6,69-7,48	≥ 5	≥ 6,5	10
180-200	7,09-7,87	≥ 5	≥ 6,5	10
190-210	7,48-8,27	≥ 5	≥ 6,5	10
200-220	7,87-8,66	≥ 5	≥ 6,5	10
210-230	8,27-9,06	≥ 5	≥ 6,5	10

SPÆNDEBÅND. 9 MM BÅND 9 MM ENDLESS WORMDRIVE HOSE CLAMPS

928093 - 928095



KODE 928093. 9 mm bånd af rustfrit stål AISI 430. Hus af rustfrit stål AISI 430. Rustfri stålskrue galvaniseret bikromat.

KODE 928095. 9mm bånd af rustfrit stål AISI 304. Hus af rustfrit stål AISI 304. Rustfri stålskrue AISI 304.

COD 928093. W2 Endless wormdrive hose clamps. Stainless steel band AISI 430 of 9 mm. Stainless steel housing AISI 430. Stainless steel screw galvanized bichromate.

COD 928095. W4 Endless wormdrive hose clamps. Stainless steel band AISI 304 of 9 mm. Stainless steel housing AISI 304. Stainless steel screw AISI 304.

W2-W4 mm 9				
SPÆNDEBÅND MÅL MIN/MAX CLAMPING RANGE MIN/MAX	SPÆNDEBÅND MÅL MIN/MAX CLAMPING RANGE MIN/MAX	MOMENT VED MONTAGE TORQUE - AT FITTING	MAX. MOMENT BRUDSTYRKE TORQUE - AT BREAK	ANTAL I KASSE PIECES FOR BOX
mm	tommer	Nm	Nm	Styk
8-12	0,31-0,47	≥ 3	≥ 5	50
10-16	3/8-5/8	≥ 3	≥ 5	50
12-20	0,47-3/4	≥ 3	≥ 5	50
16-25	5/8-1	≥ 3	≥ 5	50
20-32	25/32-1 1/4	≥ 3	≥ 5	50
25-40	0,98-1,57	≥ 3	≥ 5,5	50
32-50	1 1/4-2	≥ 3	≥ 5,5	50
40-60	19/16-2,36	≥ 3	≥ 5,5	50
50-70	2-2 3/4	≥ 3	≥ 5,5	50
60-80	2,36-3,15	≥ 3	≥ 5,5	50
70-90	2 3/4-3,54	≥ 3	≥ 5,5	50
80-100	3,15-3,94	≥ 3	≥ 5,5	10
90-110	3,54-4,33	≥ 3	≥ 5,5	10
100-120	3,94-4,72	≥ 3	≥ 5,5	10
110-130	4,33-5,12	≥ 3	≥ 5,5	10
120-140	4,72-5,51	≥ 3	≥ 5,5	10
130-150	5,12-5,91	≥ 3	≥ 5,5	10
140-160	5,51-6,3	≥ 3	≥ 5,5	10
150-170	5,92-6,69	≥ 3	≥ 5,5	10
160-180	6,3-7,09	≥ 3	≥ 5,5	10
170-190	6,69-7,48	≥ 3	≥ 5,5	10
180-200	7,09-7,87	≥ 3	≥ 5,5	10
190-210	7,48-8,27	≥ 3	≥ 5,5	10
200-220	7,87-8,66	≥ 3	≥ 5,5	10
210-230	8,27-9,06	≥ 3	≥ 5,5	10

ENKELT BOLT CLAMP BOLT GRIP COLLAR

928089



KODE 928089. W1 Bolt clamp i galvaniseret stål.

COD 928089. W1 Bolt grip collar galvanised steel.

KODE 928089 W1							
CLAMP MÅL MIN/MAX CLAMPING RANGE MIN/MAX		BÅNDBREDE BAND WIDTH	BÅNDTYKKELSE BAND THICKNESS	SKRUETYPE SCREW	MOMENT VED MONTAGE TORQUE - AT FITTING	MAX. MOMENT BRUDSTYRKE TORQUE - AT BREAK	ANTAL I KASSE PIECES FOR BOX
mm	tommer	mm	mm	mm	Nm	Nm	Styk
23-25	0,91-0,98	18	0,6	M5x40	≥ 5	≥ 7,5	20
26-28	1,02-1,10	18	0,6	M5x40	≥ 5	≥ 7,5	20
29-31	1,14-1,22	20	0,8	M6x50	≥ 7,5	≥ 15	20
32-35	1,26-1,38	20	0,8	M6x50	≥ 7,5	≥ 15	20
36-39	1,42-1,54	20	0,8	M6x50	≥ 7,5	≥ 15	20
40-43	1,57-1,69	20	0,8	M6x50	≥ 7,5	≥ 15	20
44-47	1,73-1,85	22	1,2	M6x55	≥ 7,5	≥ 15	20
48-51	1,89-2,00	22	1,2	M6x55	≥ 7,5	≥ 15	20
52-55	2,00-2,17	22	1,2	M6x55	≥ 7,5	≥ 15	20
56-59	2,20-2,32	22	1,2	M6x55	≥ 7,5	≥ 15	20
60-63	2,36-2,48	22	1,2	M6x55	≥ 7,5	≥ 15	20
64-67	2,52-2,64	22	1,5	M8x70	≥ 20	≥ 30	20
68-73	2,68-2,87	24	1,5	M8x70	≥ 20	≥ 30	20
74-79	2,91-3,11	24	1,5	M8x70	≥ 20	≥ 30	10
80-85	3,15-3,35	24	1,5	M8x70	≥ 20	≥ 30	10
86-91	3,39-3,58	24	1,5	M8x70	≥ 20	≥ 30	10
92-97	3,62-3,82	24	1,5	M8x70	≥ 20	≥ 30	10
98-103	3,86-4,06	24	1,5	M8x70	≥ 20	≥ 30	10
104-112	4,09-4,41	24	1,5	M8x80	≥ 20	≥ 30	10
113-121	4,45-4,76	24	1,5	M8x80	≥ 20	≥ 30	10
122-130	4,81-5,12	24	1,5	M8x80	≥ 20	≥ 30	10
131-139	5,16-5,47	26	1,7	M10x90	≥ 30	≥ 55	10
140-148	5,51-5,83	26	1,7	M10x90	≥ 30	≥ 55	10
149-161	5,87-6,34	26	1,7		≥ 30	≥ 55	10
162-174	6,38-6,85	26	1,7		≥ 30	≥ 55	10
175-187	6,89-7,36	26	1,7		≥ 30	≥ 55	10
188-200	7,40-7,87	26	1,7		≥ 30	≥ 55	10
201-213	7,91-8,39	26	1,7		≥ 30	≥ 55	10
214-226	8,43-8,90	26	1,7		≥ 30	≥ 55	10
227-239	8,94-9,41	26	1,7		≥ 30	≥ 55	10
240-252	9,45-9,92	26	1,7		≥ 30	≥ 55	10

- Alle gældende tekniske specifikationer er gældende ved en temperatur på 23° C ± 2° C (ISO 291)
- Tolerancen på alle specifikationer er ± 5% (Tolerance procenten gælder for ALLE VARER i vores sortiment)
- For informationer om en vare er lager- eller skaffevare, henvises til vores hjemmeside.

ENKELT BOLT CLAMP BOLT GRIP COLLAR

928090



KODE 928090. W4 Bolt clamp i rustfrit stål AISI 304.

COD 928090. W4 Bolt grip collar made of stainless steel AISI 304. Stainless steel.

KODE 928090 W4							
CLAMP MÅL MIN/MAX CLAMPING RANGE MIN/MAX		BÅNDBREDE BAND WIDTH	BÅNDTYKKELSE BAND THICKNESS	SKRUETYPE SCREW	MOMENT VED MONTAGE TORQUE - AT FITTING	MAX. MOMENT BRUDSTYRKE TORQUE - AT BREAK	ANTAL I KASSE PIECES FOR BOX
mm	tommer	mm	mm	mm	Nm	Nm	Styk
23-25	0,91-0,98	18	0,6	M5x40	≥ 5	≥ 7,5	8
26-28	1,02-1,10	18	0,6	M5x40	≥ 5	≥ 7,5	8
29-31	1,14-1,22	20	0,6	M6x50	≥ 7,5	≥ 15	8
32-35	1,26-1,38	20	0,6	M6x50	≥ 7,5	≥ 15	8
36-39	1,42-1,54	20	0,6	M6x50	≥ 7,5	≥ 15	8
40-43	1,57-1,69	20	0,6	M6x50	≥ 7,5	≥ 15	8
44-47	1,73-1,85	22	0,8	M6x55	≥ 7,5	≥ 15	8
48-51	1,89-2,00	22	0,8	M6x55	≥ 7,5	≥ 15	8
52-55	2,00-2,17	22	0,8	M6x55	≥ 7,5	≥ 15	8
56-59	2,20-2,32	22	0,8	M6x55	≥ 7,5	≥ 15	8
60-63	2,36-2,48	22	0,8	M6x55	≥ 7,5	≥ 15	8
64-67	2,52-2,64	22	0,8	M8x70	≥ 20	≥ 30	8
68-73	2,68-2,87	24	0,8	M8x70	≥ 20	≥ 30	8
74-79	2,91-3,11	24	0,8	M8x70	≥ 20	≥ 30	4
80-85	3,15-3,35	24	0,8	M8x70	≥ 20	≥ 30	4
86-91	3,39-3,58	24	0,8	M8x70	≥ 20	≥ 30	4
92-97	3,62-3,82	24	0,8	M8x70	≥ 20	≥ 30	4
98-103	3,86-4,06	24	0,8	M8x70	≥ 20	≥ 30	4
104-112	4,09-4,41	24	0,8	M8x80	≥ 20	≥ 30	4
113-121	4,45-4,76	24	0,8	M8x80	≥ 20	≥ 30	4
122-130	4,81-5,12	24	0,8	M8x80	≥ 20	≥ 30	4
131-139	5,16-5,47	26	1,0	M10x90	≥ 30	≥ 55	4
140-148	5,51-5,83	26	1,0	M10x90	≥ 30	≥ 55	4
149-161	5,87-6,34	26	1,0	M10x110	≥ 30	≥ 55	4
162-174	6,38-6,85	26	1,0	M10x110	≥ 30	≥ 55	4
175-187	6,89-7,36	26	1,0	M10x110	≥ 30	≥ 55	4
188-200	7,40-7,87	26	1,0	M10x110	≥ 30	≥ 55	4
201-213	7,91-8,39	26	1,0	M10x110	≥ 30	≥ 55	4
214-226	8,43-8,90	26	1,0	M10x110	≥ 30	≥ 55	4
227-239	8,94-9,41	26	1,0	M10x110	≥ 30	≥ 55	4
240-252	9,45-9,92	26	1,0	M10x110	≥ 30	≥ 55	4

- All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)
- The tolerance on all specifications ± 5% (Tolerance Percentage is applicable on ALL DATA across our range)
- To verify if the item of your interest is "on stock" or "on demand" pls refer to our web site.

MERLETT DENMARK

Fabriksvangen, 15
3550, Slangerup Denmark
Ph: +45 48 10 33 00
Fax: +45 48 10 33 10
industrial-hose.DK@continental.com

For further information:

www.continental-industry.com

**Legal notice**

The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2020 ContiTech AG. All rights reserved. For complete information go to: www.continental-industry.com/discl_en