

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23 °C bar	vacuum 23 °C m/H <sub>2</sub> O	bursting press. at 23 °C bar	bending radius mm	total thickness mm	Ø rigid spiral (AxB if oval) mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
16		16	20.4	6.5	6	19.5	90	2.2		5.8	right	175	30	On demand
20		20	24.9	6.5	6	19.5	110	2.4	2.3x3.6	6.5	right	210	25	In stock
25	1	25	29.7	6.5	6	19.5	140	2.4	2.3x3.3	7.4	right	250	25	In stock
30		30	35	6	6	18	175	2.5	2.4x3.8	7.3	right	330	25	In stock
32	1 1/4	32	37.2	6	6	18	180	2.6	2.4x4	7.7	right	350	25	In stock
35		35	40.4	6	6	18	195	2.7	2.6x4.2	7.7	right	400	25	In stock
38	1 1/2	38	43.6	6	6	18	210	2.8	2.5x4	7.8	right	430	25	In stock
40		40	46	5.5	6	16.5	220	3	2.6x4.5	7.5	right	480	25	In stock
45	1 3/4	45	52	5.5	6	16.5	255	3.5	3x4.7	7.8	right	640	25	In stock
50	2	50	58.4	5.5	6	16.5	275	4.2	4	8.3	right	760	25	In stock
55		55	63.8	5.5	6	16.5	310	4.4	4.1	9.8	right	860	25	In stock
60		60	68.4	4	6	12	330	4.2	4	8.3	right	900	25	In stock
63	2 1/2	63	71.2	4	6	12	350	4.1	4	8.5	right	970	25	In stock
70		70	79	3	6	9	450	4.5	4.2	8.8	right	1125	25	In stock
75		75	84.4	3	6	9	500	4.7	4.5	9	right	1200	25	In stock
80		80	89.4	3	6	9	550	4.7	4.5	10.5	right	1450	25	In stock
90	3 1/2	90	101.8	3	6	9	630	5.9	5.6	10.3	right	1850	25	On demand
100		100	112.2	2	6	6	700	6.1	5.8	11.3	right	2200	25	On demand
110		110	122	2	6	6	770	6	5.5	11.5	right	2400	25	On demand
120		121	133.4	2	4	6	840	6.2	6	11.5	right	2800	25	On demand

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

All technical specifications contained herein are provided for reference purposes only.

For further details regarding our products' specifications, please refer to the relevant products' data sheets or contact your sales representative.