

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23 °C bar	vacuum 23 °C m/H ₂ O	bursting press. at 23 °C bar	bending radius mm	total thickness mm	Ø rigid spiral (AxB if oval) mm	Strand Wire in 1 mt m	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
25	1	25	31.6	8	8	24	120	3.3	3.1	13	7.4	right	340	50	On demand
30		30	37	7	8	21	140	3.5	3.2	14	7.5	right	420	50	On demand
32	1 1/4	32	39.2	7	8	21	150	3.6	3.5	15	7.5	right	460	50	On demand
35		35	42.2	7	8	21	160	3.6	3.5	16	7.5	right	500	50	On demand
38	1 1/2	38	45.4	TBD	8	TBD	170	3.7	3.5	17.5	7.6	right	550	50	On demand
40		40	47.6	6.5	8	19.5	180	3.8	3.6	18	7.8	right	610	50	On demand
45	1 3/4	45	52.4	6	8	18	200	3.7	3.6	19	8	right	670	50	On demand
50		50	58.2	5.5	8	16.5	220	4.1	4	21	8.3	right	810	50	On demand
51	2	51	59.2	5.5	8	16.5	220	4.1	3.9	20.5	8.5	right	810	50	On demand
55		55	63.4	TBD	8	TBD	250	4.2	4	19	9.8	right	860	50	On demand
60		60	68.4	5	8	15	270	4.2	4	22	8.5	right	970	50	On demand
63	2 1/2	63.5	71.5	5	8	15	290	4	3.7	27	8.5	right	1040	50	On demand
70		70	79.2	4	8	12	320	4.6	4.2	27	8.8	right	1200	50	On demand
75		75	85.4	4	8	12	350	5.2	5	27	9.1	right	1380	50	On demand
80		80	90.6	3.5	8	10.5	360	5.3	5	27	10	right	1560	25	On demand
90	3 1/2	90	100.4	3.5	8	10.5	430	5.3	5	29	10.9	right	1850	25	On demand
100		100	112	3.5	8	10.5	480	6	5.6	29	11.3	right	2160	25	On demand
150		150	165	2.5	6	7.5	810	7.5	6.7	36.5	13.5	right	4250	25	On demand

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

All technical specifications contained herein are provided for reference purposes only.

For further details regarding our products' specifications, please refer to the relevant products' data sheets or contact your sales representative.