



RAGNO N 20 BAR 915046



PVC hose with polyester yarn reinforcement and PU adhesive intermediate layer for pressure spraying of insecticides, pesticides, and liquids under pressure.

DETAILS


 SMOOTH SURFACE * * *

 FLEXIBILITY * * *

 ABRASION RESISTANCE * * *

 TEMPERATURE RANGE -5 °C 60 °C

 CHEMICAL RESISTANCE PVC Table

 CRUSHING RESISTANCE * * *

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23 °C bar	working press. at 40 °C bar	working press. at 60 °C bar	bursting press. at 23 °C bar	bending radius mm	weight meter g/m	# wires for angle n° x a°	coil length m	Availability
6		6	12	20	16	12	60		115	12X54°	100	On demand
8	5/16	8	13	20	16	12	60	27	110	18x54°	100	In stock
8	5/16	8	14	20	16	12	60		130	18x54°	100	On demand
10	3/8	10	15	20	16	12	60	32	120	24x54°	100	In stock
10	3/8	10	16	20	16	12	60		160	24x54°	100	On demand
13	1/2	13	19	20	16	12	60	55	180	24x54°	100	In stock
16	5/8	16	23	20	16	12	60	60	300	24x55°	100	In stock
19	3/4	19	26	20	16	12	60	70	350	24x54° doppia	100	In stock
25	1	25	34	20	16	12	60	100	530	36x54° doppia	50	In stock

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

The tolerance on all specifications ±5% (Tolerance Percentage is applicable on ALL DATA across our range)