

| Ø nominal mm | Ø nominal inch | Ø i.d. mm | Ø o.d. mm | vacuum 23 °C m/H ₂ O | bending radius mm | wall thickness mm | Ø steel wire mm | spiral pitch mm | spiral direction | weight meter g/m | coil length comp. m | Availability |
|-----------------|-------------------|--------------|--------------|---------------------------------------|-------------------------|-------------------------|-----------------------|--------------------|---------------------|------------------------|---------------------------|--------------|
| 25 | | 26 | 30 | 0.4 | 5 | 0.35 | 1 | 9.5 | left | 100 | 6/10 | On demand |
| 30 | | 31 | 35 | 0.3 | 7 | 0.4 | 1 | 14 | left | 120 | 6/10 | On demand |
| 35 | | 36 | 40 | 0.28 | 8 | 0.4 | 1 | 14 | left | 140 | 6/10 | On demand |
| 40 | | 41 | 45 | 0.25 | 10 | 0.4 | 1 | 14 | left | 150 | 6/10 | On demand |
| 45 | | 46 | 50 | 0.23 | 12 | 0.4 | 1 | 14 | left | 190 | 6/10 | On demand |
| 50 | 2 | 51 | 55 | 0.2 | 13 | 0.4 | 1.2 | 18 | left | 185 | 6/10 | In stock |
| 55 | | 56 | 60 | 0.18 | 14 | 0.4 | 1.2 | 18 | left | 200 | 6/10 | On demand |
| 60 | | 61 | 65 | 0.16 | 15 | 0.4 | 1.2 | 18 | left | 220 | 6/10 | In stock |
| 63 | 2 1/2 | 64 | 68 | 0.15 | 16 | 0.4 | 1.2 | 18 | left | 230 | 6/10 | In stock |
| 70 | | 71 | 75 | 0.14 | 18 | 0.4 | 1.4 | 18 | left | 330 | 6/10 | On demand |
| 76 | 3 | 77 | 81 | 0.1 | 19 | 0.4 | 1.4 | 18 | left | 350 | 6/10 | In stock |
| 80 | | 81 | 85 | 0.1 | 20 | 0.4 | 1.4 | 18 | left | 370 | 6/10 | In stock |
| 90 | 3 1/2 | 91 | 95 | 0.1 | 22 | 0.4 | 1.4 | 18 | left | 420 | 6/10 | In stock |
| 100 | 4 | 102 | 106 | 0.09 | 20 | 0.4 | 1.6 | 23 | left | 480 | 6/10 | In stock |
| 110 | | 112 | 116 | 0.09 | 22 | 0.4 | 1.6 | 23 | left | 520 | 6/10 | In stock |
| 115 | | 117 | 121 | 0.09 | 23 | 0.4 | 1.6 | 23 | left | 545 | 6/10 | In stock |
| 120 | | 122 | 126 | 0.09 | 24 | 0.4 | 1.6 | 23 | left | 550 | 6/10 | In stock |
| 125 | 5 | 127 | 131 | 0.08 | 25 | 0.4 | 1.6 | 23 | left | 590 | 6/10 | In stock |
| 130 | | 132 | 136 | 0.08 | 26 | 0.4 | 1.6 | 23 | left | 610 | 6/10 | On demand |
| 140 | | 142 | 143 | 0.08 | 28 | 0.4 | 1.6 | 23 | left | 660 | 6/10 | In stock |
| 150 | 6 | 153 | 158 | 0.06 | 30 | 0.5 | 1.8 | 30 | left | 700 | 6/10 | In stock |
| 160 | | 163 | 168 | 0.06 | 32 | 0.5 | 1.8 | 30 | left | 750 | 6/10 | In stock |
| 170 | | 173 | 178 | 0.06 | 34 | 0.5 | 1.8 | 30 | left | 780 | 6/10 | On demand |
| 180 | | 183 | 188 | 0.06 | 36 | 0.5 | 1.8 | 30 | left | 830 | 6/10 | In stock |
| 200 | 8 | 203 | 208 | 0.05 | 40 | 0.5 | 1.8 | 30 | left | 920 | 6/10 | In stock |
| 220 | | 223 | 228 | 0.05 | 45 | 0.5 | 1.8 | 30 | left | 1070 | 6/10 | In stock |
| 250 | 10 | 254 | 260 | 0.04 | 50 | 0.6 | 2 | 36 | left | 1250 | 6/10 | In stock |
| 280 | | 284 | 290 | 0.04 | 55 | 0.6 | 2 | 36 | left | 1350 | 6/10 | On demand |
| 300 | 12 | 304 | 310 | 0.03 | 60 | 0.6 | 2 | 36 | left | 1500 | 6/10 | In stock |
| 315 | | 319 | 325 | 0.03 | 62 | 0.6 | 2 | 36 | left | 1150 | 6/10 | On demand |
| 325 | | 329 | 335 | 0.03 | 65 | 0.6 | 2 | 36 | left | 1600 | 6/10 | On demand |
| 350 | | 354 | 360 | 0.03 | 70 | 0.6 | 2 | 36 | left | 1750 | 6/10 | In stock |
| 400 | | 405 | 412 | 0.02 | 80 | 0.6 | 2 | 36 | left | 2000 | 6/10 | In stock |
| 450 | | 456 | 462 | 0.01 | 90 | 0.6 | 2 | 36 | left | 2300 | 6 | On demand |
| 500 | | 505 | 512 | 0.01 | 100 | 0.6 | 2 | 36 | left | 2500 | 6 | In stock |
| 550 | | 555 | 562 | 0.01 | 110 | 0.6 | 2 | 36 | left | 2700 | 6 | On demand |
| 600 | | 605 | 612 | 0.01 | 120 | 0.6 | 2 | 36 | left | 3000 | 6 | In stock |

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

All technical specifications contained herein are provided for reference purposes only.

For further details regarding our products' specifications, please refer to the relevant products' data sheets or contact your sales representative.