











## ARMORVIN HNA

913040



Plasticized PVC hose with embedded galvanised steel spiral, for suction and delivery of liquids and liquid food stuffs.

### DETAILS

	SMOOTH SURFACE	*****
	FLEXIBILITY	****
	ABRASION RESISTANCE	***
	TEMPERATURE RANGE	-5 °C 65 °C
	CHEMICAL RESISTANCE	PVC Table
	CRUSHING RESISTANCE	***
	FOR FOOD	product.tech.for_food_eu_voice.Suitable for contact with foodstuffs according to declaration of conformity. FDA according to Declaration of Conformity
	O-PHTALATE FREE	*****

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	vacuum 23 °C m/H <sub>2</sub> O	working press. at 23 °C r.1:3 bar	bursting press. at 23 °C bar	bending radius mm	total thickness mm	Ø steel wire mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
10	3/8	10	16	8.5	7	21	20	3	0.8	6.5	right	155	60	In stock
12		12	18	8.5	7	21	25	3	0.8	7	right	180	60	In stock
14		14	20	8.5	6	18	30	3	0.8	7.5	right	200	60	In stock
16	5/8	16	22	8.5	6	18	35	3	0.8	7.5	right	225	60	In stock
18		18	24.5	8.5	6	18	40	3.25	1	8	right	280	60	In stock
19	3/4	19	26	8.5	5	15	45	3.5	1	8	right	310	60	On demand
20		20	27	8.5	5	15	50	3.5	1	8	right	340	60	In stock
22	7/8	22	29	8.5	5	15	55	3.5	1	8.5	right	360	60	In stock
25	1	25	33	8.5	5	15	60	4	1.4	13.5	right	510	60	In stock
30		30	39	8.5	4.5	13.5	70	4.5	1.4	13.5	right	600	60	On demand
32	1 1/4	32	41	8.5	4.5	13.5	75	4.5	1.4	13.5	right	650	60	In stock
35		35	44	8.5	4	12	80	4.5	1.4	14.5	right	730	60	In stock
38	1 1/2	38	47	8.5	4	12	90	4.5	1.6	15	right	800	30	In stock
40		40	49.5	8.5	3	9	95	4.75	1.6	15	right	870	30	In stock
45	1 3/4	45	55	8	3	9	110	5	1.8	15	right	1100	30	In stock
50	2	50	60	8	3	9	125	5	1.8	16	right	1200	30	In stock
55		55	66	8	3	9	130	5.5	1.8	16.5	right	1380	30	On demand
60		60	72	8	2.5	7.5	140	6	2.5	20	right	1800	30	In stock
63	2 1/2	63	75	8	2.5	7.5	150	6	2.5	20	right	1880	30	In stock
70		70	83	8	2	6	170	6.5	2.5	20	right	2200	30	On demand
75		75	89	7	2	6	200	7	2.5	20	right	2500	30	In stock
80		80	94	7	2	6	220	7	2.5	20	right	2700	30	In stock
90	3 1/2	90	104	7	2	6	260	7	2.5	20	right	2900	30	On demand
100		100	114	7	2	6	300	7	2.5	19	right	3250	30	In stock

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

All technical specifications contained herein are provided for reference purposes only.

For further details regarding our products' specifications, please refer to the relevant products' data sheets or contact your sales representative.