



POLIPO 15 BAR OIL

915133



Plastic hose with POLYURETHANE (PU) underlayer with polyester yarn reinforcement and PU adhesive middle layer, for pressurized transfer of oil, diesel oil, blue diesel, urea (ISO 22241).

DETAILS

	SMOOTH SURFACE	*****
	FLEXIBILITY	***
	ABRASION RESISTANCE	***
	TEMPERATURE RANGE	-10 °C 60 °C
	CHEMICAL RESISTANCE	PU Table
	CRUSHING RESISTANCE	***

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23 °C bar	working press. at 40 °C bar	working press. at 60 °C bar	bursting press. at 23 °C bar	bending radius mm	weight meter g/m	# wires for angle n° x a°	coil length m	Availability
12.7	1/2	12.7	18.5	15	10	6	45	80	205	18x54°	100	On demand
19	3/4	19	26	15	10	6	45	130	350	24x54°	60	In stock
19.5	3/4	19.2	26.5	15	10	6	45	130	360	24X54°	60	On demand
25	1	25	35	15	10	6	45	180	640	36x54°	60	In stock

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

All technical specifications contained herein are provided for reference purposes only.

For further details regarding our products' specifications, please refer to the relevant products' data sheets or contact your sales representative.