

Nenn-Ø mm	Nenn-Ø inch	Innen-Ø mm	Aussen-Ø mm	Betriebsdruck bei 23 °C bar	Vakuum bei 23 °C m/H <sub>2</sub> O	Platzdruck bei 23 °C bar	Biegeradius mm	Gesamtstärke mm	Hartspirale mm	Spiralsteigung mm	Spiralrichtung	Gewicht je Meter g/m	Rollenlänge m	Beschaffbarkeit
25	1	25	35	11	9	33	160	5		5	rechts	600	30	Auf anfrage
32	1 1/4	32	42	9	9	27	190	5		5.7	rechts	700	30	Auf anfrage
38	1 1/2	38	48	9	9	27	230	5		5.8	rechts	800	30	Auf anfrage
51	2	51.3	62.1	7	9	21	290	5.4	4.8	8.6	rechts	1200	30	Ab lager
63	2 1/2	63.5	76.5	7	9	21	360	6.5	5.8	10	rechts	1700	30	Ab lager
76	3	76.2	89.6	6	9	18	450	6.7	5.8	11.5	rechts	2000	30	Ab lager
80		80	93.4	6	9	18	500	6.7	6	12	rechts	2200	30	Ab lager
90	3 1/2	90	103.6	6	9	18	560	6.8	6.5	10.3	rechts	2500	30	Ab lager
100		100	115	4.5	9	13.5	620	7.5	7	11.3	rechts	3300	30	Ab lager
102	4	102	117	4.5	9	13.5	640	7.5	7	11.3	rechts	3300	30	Ab lager
110		110	126	4.5	9	13.5	800	8	7.5	11.5	rechts	3900	30	Auf anfrage
127	5	127	143.8	4.5	9	13.5	860	8.4	7.3	12.5	rechts	4200	30	Ab lager
152	6	152.4	171.6	2.5	9	7.5	1100	9.6	8.8	16	rechts	5900	20	Ab lager
200		200	226	2	9	6	1200	13	12	22	rechts	10500	15	Ab lager
203	8	203.4	229.4	2	9	6	1300	13		22	rechts	10500	15	Ab lager

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

All technical specifications contained herein are provided for reference purposes only.

For further details regarding our products' specifications, please refer to the relevant products' data sheets or contact your sales representative.