

Nenn-Ø mm	Nenn-Ø inch	Innen-Ø mm	Aussen-Ø mm	Vakuum bei 23 °C m/H ₂ O	Biegeradiu s mm	Wandstärk e mm	Ø Stahldraht mm	Spiralsteig ung mm	Spiralricht ung	Gewicht je Meter g/m	Rollenläng e m	Beschaffba rkeit
25	1	25.5	28.5	0.4	50	0.3	1	7	rechts	130	30	Ab lager
30		30.5	33.5	0.4	60	0.3	1	8	rechts	145	30	Ab lager
32		32.5	35.5	0.35	65	0.3	1	8	rechts	150	30	Auf anfrage
35		35.5	38.5	0.28	70	0.3	1	8	rechts	160	30	Ab lager
38		38.5	41.5	0.25	75	0.35	1	8.5	rechts	180	30	Auf anfrage
40		40.5	44	0.23	80	0.35	1	8.5	rechts	190	30	Ab lager
45	1 3/4	45.5	49	0.2	90	0.35	1	9.5	rechts	200	30	Ab lager
50		50.5	54	0.18	100	0.35	1	9.5	rechts	215	30	Ab lager
51	2	51.5	55	0.18	100	0.35	1	9.5	rechts	220	30	Auf anfrage
55		55.5	59	0.15	110	0.35	1	9.5	rechts	240	30	Ab lager
60		60.5	64	0.14	120	0.35	1	10.5	rechts	250	30	Ab lager
63	2 1/2	63.5	67	0.1	125	0.35	1	10.5	rechts	260	30	Ab lager
65		65.5	69	0.1	130	0.35	1	10.5	rechts	270	30	Auf anfrage
70		70.5	75	0.1	140	0.35	1.3	12.5	rechts	320	30	Ab lager
75		75.5	80	0.09	150	0.35	1.3	12.5	rechts	360	30	Ab lager
76	3	76.5	81	0.09	155	0.35	1.3	12.5	rechts	360	30	Ab lager
80		80.5	85	0.09	160	0.4	1.3	14	rechts	400	30	Ab lager
90	3 1/2	91	96	0.09	180	0.4	1.3	14.5	rechts	420	30	Ab lager
100		101	106	0.08	200	0.4	1.3	15.5	rechts	430	30	Ab lager
102	4	103	108	0.08	205	0.4	1.3	15.5	rechts	440	30	Auf anfrage
110		111	116	0.08	220	0.4	1.3	16	rechts	460	30	Ab lager
120		121	126	0.06	240	0.4	1.3	16	rechts	480	30	Ab lager
125		126	131	0.06	250	0.4	1.3	16	rechts	540	30	Ab lager
130		131	136	0.06	260	0.4	1.3	16	rechts	580	30	Ab lager
140		141	146	0.06	280	0.4	1.3	16	rechts	600	30	Ab lager
150		153	158	0.05	300	0.4	1.6	17	rechts	800	30	Ab lager
160		161.5	166	0.05	320	0.4	1.6	18	rechts	820	30	Ab lager
180		183.5	188	0.04	360	0.4	1.6	20	rechts	900	20	Ab lager
200		204	209	0.04	400	0.4	1.6	20	rechts	980	20	Ab lager
250		254	260	0.03	500	0.45	1.8	22	rechts	1460	10	Ab lager
300		306	312	0.03	600	0.45	1.8	28	rechts	1560	10	Ab lager

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

All technical specifications contained herein are provided for reference purposes only.

For further details regarding our products' specifications, please refer to the relevant products' data sheets or contact your sales representative.