

Nenn-Ø mm	Nenn-Ø inch	Innen-Ø mm	Aussen-Ø mm	Betriebsdruck bei 23 °C bar	Betriebsdruck bei 40 °C bar	Betriebsdruck bei 60 °C bar	Platzdruck bei 23 °C bar	Biegeradius s mm	Gewicht je Meter g/m	Drahtwinkel el n° x a°	Rollenlänge e m	Beschaffbarkeit
12.5	1/2	12.5	21	20	18	12	60	50	300	24x54° doppia	100	Auf anfrage
13	1/2	13	22	20	16	12	60	50	350	24x54° doppia	60	Auf anfrage
15	5/8	15	23	20	16	12	60	60	310	24x54° doppia	60	Auf anfrage
16	5/8	16	25.5	20	16	12	60	60	400	24x54° doppia	60	Auf anfrage
19	3/4	19	27	20	16	12	60	80	390	24x54° doppia	60	Ab lager
19	3/4	19	30	20	16	12	60	70	520	24x54° doppia	60	Auf anfrage
25	1	25	34.5	20	16	12	60	120	600	36x54° doppia	60	Ab lager
25	1	25	37	20	16	12	60	120	730	36x54° doppia	60	Auf anfrage
32	1-1/4	32	43.5	20	16	12	60	150	850	36x54° doppia	60	Auf anfrage

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

All technical specifications contained herein are provided for reference purposes only.

For further details regarding our products' specifications, please refer to the relevant products' data sheets or contact your sales representative.