

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23 °C bar	vacuum 23 °C m/H ₂ O	bursting press. at 23 °C bar	bending radius mm	total thickness mm	Ø rigid spiral (AxB if oval) mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
25	1	25	35	11	9	33	160	5		5	right	600	30	On demand
32	1 1/4	32	42	9	9	27	190	5		5.7	right	700	30	On demand
38	1 1/2	38	48	9	9	27	230	5		5.8	right	800	30	On demand
51	2	51.3	62.1	7	9	21	290	5.4	4.8	8.6	right	1200	30	On demand
63	2 1/2	63.5	76.5	7	9	21	360	6.5	5.8	10	right	1700	30	On demand
76	3	76.2	89.6	6	9	18	450	6.7	5.8	11.5	right	2000	30	On demand
80		80	93.4	6	9	18	500	6.7	6	12	right	2200	30	On demand
90	3 1/2	90	103.6	6	9	18	560	6.8	6.5	10.3	right	2500	30	On demand
100		100	115	4.5	9	13.5	620	7.5	7	11.3	right	3300	30	On demand
102	4	102	117	4.5	9	13.5	640	7.5	7	11.3	right	3300	30	On demand
110		110	126	4.5	9	13.5	800	8	7.5	11.5	right	3900	30	On demand
127	5	127	143.8	4.5	9	13.5	860	8.4	7.3	12.5	right	4200	30	On demand
152	6	152.4	171.6	2.5	9	7.5	1100	9.6	8.8	16	right	5900	20	On demand
200		200	226	2	9	6	1200	13	12	22	right	10500	15	On demand
203	8	203.4	229.4	2	9	6	1300	13		22	right	10500	15	On demand

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

All technical specifications contained herein are provided for reference purposes only.

For further details regarding our products' specifications, please refer to the relevant products' data sheets or contact your sales representative.