



# ALABAMA

911194



PVC hose with rectangular rigid PVC spiral, for suction and delivery of liquids, irrigation systems, and cleaning sewage drains and cesspits.

## DETAILS

SMOOTH SURFACE \*\*\*\*\*

FLEXIBILITY \*\*\*\*

ABRASION RESISTANCE \*\*\*

TEMPERATURE RANGE -25 °C 55 °C

CHEMICAL RESISTANCE PVC Table

CRUSHING RESISTANCE \*\*\*\*

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23 °C bar	vacuum 23 °C m/H <sub>2</sub> O	bursting press. at 23 °C bar	bending radius mm	total thickness mm	Rigid wire size mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
51	2	50.8	58.8	5	9	15	220	4	3.6x7.4	10.5	right	850	50	On demand
63	2 1/2	63	71.4	4	9	12	250	4.2	3.5x7.5	11	right	1150	50	On demand
76	3	76.2	85.2	4	9	12	330	4.5	4x8.5	13	right	1450	30	On demand
80		80	89.6	4	9	12	350	4.8	4.4x9	14.5	right	1600	30	On demand
90		90	100	3	9	9	400	5	4.5x10.3	14.5	right	2000	30	On demand
102	4	101.6	111.6	3	9	9	430	5	4.7x10.3	14.5	right	2200	30	On demand
110		110	121.4	2.5	9	7.5	480	5.7	4.7x10.5	15.5	right	2700	20	On demand
120		120	131.6	2.5	9	7.5	520	5.8	5x10.5	17	right	2950	30	On demand
127	5	127	139	2.5	9	7.5	550	6	10.5x5.5	17.5	right	3200	20	On demand
133		133	146	2	9	6	600	6.5	6x11.5	18	right	3400		On demand
152	6	152.4	166.4	2	9	6	700	7	6.5x12.3	19.5	right	4300		On demand
160		160	175	2	9	6	800	7.5	7x13	21.5	right	4550		On demand
203	8	203.2	223.2	1.5	9	4.5	900	10	10x14.2	22.5	right	8500		On demand

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

The tolerance on all specifications ±5% (Tolerance Percentage is applicable on ALL DATA across our range)