

RAGNO N 40 BAR

915048

PVC hose with polyester yarn reinforcement and PU adhesive intermediate layer for pressure spraying of insecticides, pesticides, and liquids under pressure.

DETAILS

SMOOTH SURFACE	✶✶✶✶✶
FLEXIBILITY	✶✶✶✶
ABRASION RESISTANCE	✶✶✶
TEMPERATURE RANGE	-5 °C 60 °C
CHEMICAL RESISTANCE	PVC Table
CRUSHING RESISTANCE	✶✶✶

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23 °C bar	working press. at 40 °C bar	working press. at 60 °C bar	bursting press. at 23 °C bar	bending radius mm	weight meter g/m	# wires for angle n° x a°	coil length m	Availability
8	5/16	8	13.5	40	32	24	120	25	110	18x54°	100	In stock
10	3/8	10	16	40	32	24	120	30	160	24x50°	100	In stock
13	1/2	13	21	40	32	24	120	50	290	32+32 doppia	100	In stock
19	3/4	19	28	40	32	24	120	60	475	32+32 doppia	60	On demand

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)
All technical specifications contained herein are provided for reference purposes only.
For further details regarding our products' specifications, please refer to the relevant products' data sheets or contact your sales representative.