



SUPER RAGNO N 80 BAR 915065



PVC hose with double polyester yarn reinforcement and PU adhesive intermediate layer for pressure spraying of insecticides, pesticides, and liquids under pressure.

DETAILS



SMOOTH SURFACE



FLEXIBILITY



ABRASION RESISTANCE



TEMPERATURE RANGE

-5 °C 60 °C



CHEMICAL RESISTANCE

PVC Table



CRUSHING RESISTANCE

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23 °C bar	working press. at 40 °C bar	working press. at 60 °C bar	bursting press. at 23 °C bar	bending radius mm	total thickness mm	weight meter g/m	# wires for angle n° x a°	coil length m	Availability
8	5/16	8	15	80	64	48	240	20	3.5	170	24x54° doppia	100	In stock
10	3/8	10	19	80	64	48	240	30	4.5	240	24x54° doppia	100	In stock
13	1/2	13	23	80	64	48	240	40	5	340	32x52°/54° doppia	100	In stock
16	5/8	16	26	80	64	48	240	55	5	450	36x52°/54° doppia	50	On demand

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

All technical specifications contained herein are provided for reference purposes only.

For further details regarding our products' specifications, please refer to the relevant products' data sheets or contact your sales representative.