


EVA INDUSTRIAL

918010



Hose made of spiral EVA, unreinforced, for extraction of air, dust, welding fumes and gases.

DETAILS

 SMOOTH SURFACE **

 FLEXIBILITY ****

 ABRASION RESISTANCE ***

 TEMPERATURE RANGE -30 °C 60 °C

 CHEMICAL RESISTANCE EVA Table

 CRUSHING RESISTANCE **

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	vacuum 23 °C m/H ₂ O	bending radius mm	total thickness mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
25	1	25	32.5	5	66	4	4.6	left	200	30	In stock
29		29	36	5	76	3.5	4.3	left	210	30	In stock
32	1 1/4	32	40.4	5	82	4.5	4.7	left	280	30	In stock
38	1 1/2	38	48	5	93	5	5.3	left	380	30	In stock
45	1 3/4	45	55	5	110	5	5.5	left	450	30	On demand
50	2	50	61	5	122	5.5	5.7	left	550	30	In stock
60		60	72	4	146	6	5.7	left	700	30	In stock
75		75	88.5	4	155	6.5	6.5	left	920	15	On demand
80		80	93	4	170	7	6.5	left	980	15	On demand

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

All technical specifications contained herein are provided for reference purposes only.

For further details regarding our products' specifications, please refer to the relevant products' data sheets or contact your sales representative.