

Nimelliskoko mm	Nimelliskoko inch	Sisähalkaisija mm	Ulkohalkaisija mm	Työpaine - 23 °C bar	Työpaine - 40 °C bar	Työpaine - 60 °C bar	Räjähdyssaine - 23 °C bar	Kokonaispaksuus mm	Paino g/m	n° x a°	kg	vetolujuus kg	Kieppipituus m	Saatavuus
51	2	51	55	5.5	4	2	17	2	410	36x75°	250	575	50/100	Varastosta
60		60	65	6	4.5	2.5	18	2.5	550	48x78°	450	1055	50/100	Tilauksesta
63	2 1/2	63.5	68.5	6	4.5	2.5	18	2.5	570	48x78°	480	1115	50/100	Tilauksesta
70		70	75	6	4.5	2.5	18	2.5	650	48x78°	535	1245	50/100	Tilauksesta
76	3	76	81	6	4.5	2.5	18	2.5	710	60x75°	600	1390	50/100	Varastosta
80		80	85	6	4.5	2.5	18	2.5	750	60x76°	620	1440	50/100	Tilauksesta
90	3 1/2	90	95	6	4.5	2.5	18	2.5	860	60x80°	700	1630	50/100	Tilauksesta
102	4	102	107	5	3	2	15	3	1000	72x78°	785	1825	50/100	Varastosta
110		110	116	5	3	2	15	3	1150	72x80°	865	2015	50/100	Tilauksesta
127	5	127	133	5	3	2	15	3	1350	72x80°	970	2255	50/100	Varastosta
152	6	152	158	4	3	1	12	3	1600	72x80°	1080	2520	50/100	Tilauksesta
204	8	204	210	1.5	1	0.5	5	3	2400	120x78°	1495	3480	50	Tilauksesta

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

All technical specifications contained herein are provided for reference purposes only.

For further details regarding our products' specifications, please refer to the relevant products' data sheets or contact your sales representative.