

Ø Nominal mm	Ø Nominal inch	Ø Interieur mm	Ø Exterieur mm	Pression De Service - 23 °C bar	Pression De Service - 40 °C bar	Pression De Service - 60 °C bar	Pression eclatement - 23 °C bar	Rayon De Courbure mm	Epaisseur Totale mm	Poids g/m	N° fili de Traduction/ visibilité n° x a°	Longueur Couronnes m	Disponibilit e
4		4	10	20	16	12	60	12	3	80	12x45°	100	en stock
5	3/16	5	11	20	16	12	60	15	3	90	12x45°	100	en stock
6	1/4	6	11	20	16	12	60	19	2.5	80	12x50°	100	en stock
6	1/4	6	12	20	16	12	60	17	3	105	12x54°	100	en stock
6	1/4	6	14	20	16	12	60	15	4	145	12x50°	100	sur demande
7		7	13	20	16	12	60	20	3	115	16x45°	100	en stock
8	5/16	8	13	18	13	9	54	28	2.5	105	16x50°	100	en stock
8	5/16	8	14	18	13	9	54	30	3	125	16x50°	100	sur demande
9		9	15	18	13	9	54	30	3	135	18x50°	100	sur demande
10	3/8	10	15	18	13	9	54	36	2.5	120	18x50°	100	en stock
10	3/8	10	16	18	13	9	54	30	3	150	18x54°	100	en stock
12		12	17	12	9	6	36	35	2.5	140	18x52°	50	en stock
12		12	18	12	9	6	36	35	3	180	18x52°	50	en stock
13	1/2	13	18	12	9	6	36	43	2.5	150	18x52°	50	en stock
13	1/2	13	19	12	9	6	36	52	3	175	18x52°	50	en stock
15		15	21	10	7	4	30	60	3	215	24x50°	50	en stock
15		15	23	10	7	4	30	60	4	280	24x50°	50	sur demande
16	5/8	16	21	10	7	4	30	62	2.5	185	24x50°	50	en stock
16	5/8	16	22	10	7	4	30	60	3	210	24x50°	50	en stock
19	3/4	19	25	10	7	4	30	70	3	260	24x54°	50	en stock
19	3/4	19	26	10	7	4	30	70	3.5	300	24x54°	50	en stock
22		22	30	8	5	3	24	85	4	420	24x54°	50	en stock
25	1	25	32	8	5	3	24	150	3.5	390	24x54°	50	en stock
25	1	25	33	8	5	3	24	110	4	450	24x54°	50	en stock
28		28	36	8	5	3	24	130	4	510	24x54°	25	sur demande
30		30	38	8	5	3	24	170	4	560	24x54°	50	en stock
32	1 1/4	32	42	8	4	2	24	200	5	700	36x50°	50	en stock
35		35	45	8	4	2	24	250	5	750	36x54°	50	en stock
38	1 1/2	38	48	8	4	2	24	300	5	850	48x54°	50	en stock
40		40	50	8	4	2	24	350	5	880	48x54°	50	en stock
50	2	50	62	8	4	2	24	450	6	1350	48x54°	25	en stock

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

All technical specifications contained herein are provided for reference purposes only.

For further details regarding our products' specifications, please refer to the relevant products' data sheets or contact your sales representative.