

Ø nominale mm	Ø nominale inch	Ø interno mm	Ø esterno mm	Press. eserc. a 23 °C bar	Depress. eserc. a 23 °C m/H ₂ O	Press. scoppio a 23 °C bar	Raggio curvatura mm	Spess. totale mm	Ø filo rigido (AxB se ovale) mm	Passo spirale mm	Direzione spirale	Peso metro g/m	Lungh. rotolo m	Disponibilit à
20		20	24.9	5.5	6	16.5	80	2.4	2.3x3.6	6.5	dx	210	50	Su richiesta
25	1	25	29.7	5	6	15	100	2.4	2.3x3.3	7.4	dx	250	50	Su richiesta
30		30	35	4.5	6	13.5	120	2.5	2.4x3.8	7.5	dx	330	50	Su richiesta
32	1 1/4	32	37.2	4	6	12	130	2.6	2.4x4	7.7	dx	350	50	Su richiesta
35		35	40.4	4	6	12	140	2.7	2.6x4.2	7.7	dx	400	50	Su richiesta
38	1 1/2	38	43.6	3.5	6	10.5	150	2.8	2.6x4.1	7.8	dx	430	50	Su richiesta
40		40	46	3.5	6	10.5	160	3	2.6x4.5	7.8	dx	480	50	Su richiesta
45	1 3/4	45	52	3	6	9	180	3.5	3x4.7	7.8	dx	640	50	Su richiesta
50	2	50	58.2	3	6	9	200	4.1	4	8.3	dx	760	50	Su richiesta
51	2	51	59.5	3	6	9	205	4.1		8.5	dx	760	50	Su richiesta
55		55	63.6	3	6	9	220	4.3		9.8	dx	860	50	Su richiesta
60		60	68.4	2.5	6	7.5	240	4.2	4	8.3	dx	900	50	Su richiesta
63	2 1/2	63	71.2	2.5	6	7.5	250	4.1	3.9	8.5	dx	970	50	Su richiesta
65		65	73.2	2.5	6	7.5	260	4.1		8.1	dx	1030	50	Su richiesta
70		70	79	2	6	6	280	4.5	4.2	8.8	dx	1125	50	Su richiesta
75		75	84.4	2	6	6	300	4.7	4.5	9	dx	1200	50	Su richiesta
80		80	89.4	2	6	6	320	4.7	4.4	10.5	dx	1450	25	Su richiesta
90	3 1/2	90	101.8	2	6	6	360	5.9		10.3	dx	1850	25	Su richiesta
100	4	100	112.2	1.5	6	3.5	400	6.1	4.7	11.3	dx	2200	25	Su richiesta
110		110	122	1.5	6	3.5	440	6		11.5	dx	2500	25	Su richiesta
120		120	133.4	1.5	4	3.5	500	6.2		11.5	dx	2800	25	Su richiesta

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

All technical specifications contained herein are provided for reference purposes only.

For further details regarding our products' specifications, please refer to the relevant products' data sheets or contact your sales representative.