

Średnica nominalna w mm	Średnica nominalna w calach inch	Średnica wewnętrzna mm	Średnica zewnętrzna mm	Podciśnienie - 23 °C m/H ₂ O	Promień gębia mm	grubość ścianki mm	Średnica pręta nylonowego mm	Skok spirali mm	Kierunek spirali	Ciężar metra bieżącego g/m	Wytrzymałość na rozciąganie kg	Długość zwoju m	Dostępność
50	2	52	62	5	80	0.35	3.5x6	20	lewo	330	>130	30	W magazynie
60		64	74	3.5	90	0.35	3.5x6	20	lewo	400	>130	30	W magazynie
75		77	87	1.5	100	0.35	3.5x6	20	lewo	480	>130	30	W magazynie
100		103	114	1	150	0.35	4x6.5	20	lewo	700	>130	30	W magazynie
125		128	139	0.8	200	0.35	4x6.5	20	lewo	850	>130	30	W magazynie
150		153	164	0.6	230	0.35	5x7.5	25	lewo	1200	>130	30	W magazynie
200		205	216	0.5	300	0.35	5x7.5	25	lewo	1600	>130	20	W magazynie

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

All technical specifications contained herein are provided for reference purposes only.

For further details regarding our products' specifications, please refer to the relevant products' data sheets or contact your sales representative.