

Ø Nominell mm	Ø Nominell inch	Ø Id mm	Ø Yd mm	Arbetsstryck vid 23 °C bar	Vacuum vid 23 °C m/H ₂ O	Sprängtryck vid 23 °C bar	Böjradie mm	Total tjocklek mm	Ø hård spiral mm	Spiralstigni ng mm	Spiralriktni ng	Vikt per meter g/m	Längd på rulle m	Tillgänglig het
51	2	50.8	61.8	3	9	9	165	5.5	4.8	9	höger	1100	30	I Lager
63	2 1/2	63.5	75.5	3	9	9	205	6	5.3	11	höger	1450	30	I Lager
76	3	76.2	89.2	3	9	9	260	6.5	6	11.5	höger	1800	30	I Lager
80		80	94	3	9	9	280	7	6.5	10.5	höger	1900	30	På Förfrågan
89	3 1/2	89	103	2.5	9	7.5	300	7	6.5	11.8	höger	2250	30	På Förfrågan
102	4	101.6	117	2	9	6	330	7.7	6.7	13	höger	2800	30	I Lager
110		110	126.4	1.5	9	4.5	360	8.2	7.2	11.5	höger	3400	20	På Förfrågan
127	5	127	144	1	9	3	420	8.5	7.8	14	höger	4000	20	I Lager
152	6	152.4	170	1	9	3	510	8.8	8.5	15	höger	5000	20	I Lager

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

All technical specifications contained herein are provided for reference purposes only.

For further details regarding our products' specifications, please refer to the relevant products' data sheets or contact your sales representative.